



FRAME TYPES
SCALE: 1/4" = 1'-0"



DOOR TYPES
SCALE: 1/4" = 1'-0"



FRAME DETAILS
SCALE: 1-1/2" = 1'-0"

DOOR SCHEDULE

DOOR NO	ROOM NAME	DOOR					FRAME		DETAILS			FIRE RATING	BALLISTIC RATING	GLZ	HDW SET	SIGN TYPE	FOOTNOTES
		TYPE	MAT	WIDTH	HEIGHT	THICK	TYPE	MAT	HEAD	JAMB	SILL						
FIRST FLOOR - AREA A																	
A101	SECURE VESTIBULE	SFG	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H2	J2	S2	--	--	IGL1	3	12A	1
A102	CORRIDOR	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A102A	CORRIDOR	F	SHM	3'-0"	7'-0"	2"	F1	SHM	H5	J5	--	1 1/2 HR.	--	--	DH-4.0	--	--
A103	HALL	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A103A	HALL	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A104	HOLDING	HG1	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A105	HOLDING	HG1	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A106	SALLY PORT	OHS	STL	10'-0"	10'-0"	--	--	STL	H1	J1	S1	--	--	--	--	--	ELEC. OPER. 1
A106A	SALLY PORT	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	SG1	2	--	1
A106B	SALLY PORT	OHS	STL	20'-0"	10'-0"	--	--	STL	H3	J3	S3	--	--	--	--	--	ELEC. OPER. 1
A106C	SALLY PORT	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H2	J2	S2	--	--	--	3	12A	1
A107	SALLY PORT	OHS	STL	18'-0"	10'-0"	--	--	STL	H1	J1	S1	--	--	--	--	--	ELEC. OPER. 1
A107A	WATER SERVICE	--	--	3'-0"	7'-0"	--	--	--	--	--	--	--	--	--	--	--	CHAIN/LINK FENCE GATE
A108	LARGE PROPERTY STORAGE	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	4	--	3
A109	SALLY PORT	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A109A	SALLY PORT	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A110	FEMALE HOLDING	HG1	SHM	3'-0"	7'-0"	2"	F3	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A111	SALLY PORT	SFG	SHM	3'-0"	7'-0"	2"	F2	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A112	MALE HOLDING	HG1	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A113	MALE HOLDING	HG1	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A114	STORAGE	F	SHM	3'-0"	7'-0"	2"	F1	SHM	H4	J4	--	1/2 HR.	--	--	DH-3.0	--	3
A115	HOLDING	HG1	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A116	HOLDING	HG1	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A117	HOLDING	HG1	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A118	HOLDING	HG1	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	1/2 HR.	--	SG2	DH-2.0	--	1
A119	PROPERTY STORAGE	F	SHM	3'-0"	7'-0"	2"	F1	SHM	H4	J4	--	1/2 HR.	--	--	DH-3.0	--	3
A120	CORRIDOR	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	1 1/2 HR.	--	SG3	DH-1.0	--	1
A121	PROCESS DESK	NL	SHM	3'-0"	7'-0"	2"	F1	SHM	H4	J4	--	--	--	SG1	DH-2.0	--	3
A122	VIDEO ARRANGMENT	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A123	VIDEO ARRANGMENT	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A124	PHLEBOTOMIST	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A125	FINGER PRINTING	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A126	CORRIDOR	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	1
A126A	SALLY PORT	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	2
A128	CORRIDOR	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	SG1	5	--	4
A128A	PROBATION OFFICE	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A128B	PROBATION OFFICE	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A128C	PROBATION OFFICE	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A128D	PROBATION OFFICE	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A128E	PROBATION OFFICE	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	1/2 HR.	--	SG2	4A	--	3
A128F	ELEC./DATA	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	--	6	--	--
A129	OFFICE	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	GL1	7	--	--
A130	OFFICE	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	GL1	7	--	--
A131	WORKSTATIONS	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	--	5	--	6
A131A	WORKSTATIONS	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	GL1	4	--	3
A132	CONTROL ROOM	F	SHM	3'-0"	7'-0"	2"	F1	SHM	H5	J5	--	1/2 HR.	--	--	DH-2.0	--	5
A133	TOILET ROOM	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	8	3R	--
A134	HALL	--	--	3'-0"	7'-0"	--	F1	HM	H5 SIM	J5 SIM.	--	--	--	--	--	--	CASED OPNG
A135	WOMEN'S LOCKER ROOM	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	9	3WL	3
A136	MEN'S LOCKER ROOM	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	9	3ML	3
A138	VESTIBULE	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	EX	EX	12A	--
A139	LOBBY	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	EX	EX	12A	--
A140	TOILET ROOM	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	--	EX	3R	--
A141	DUTY SUPPORT	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	GL1	10	--	3
A142	INTERVIEW	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	GL1	4A	--	3
A142A	INTERVIEW	NL	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	GL1	5	--	4
A144	VISITATION	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	EX	EX	--	--
A145	SALLY PORT	EX	SHM	3'-0"	7'-0"	2"	EX	HM	--	--	--	--	--	EX	EX	--	--
A146	SALLY PORT/ CORRIDOR	EX	SHM	3'-0"	7'-0"	2"	EX	HM	--	--	--	--	--	EX	EX	--	--
A146A	SALLY PORT/ CORRIDOR	SFG	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	--	--	SG1	DH-2.0	--	1
A147	VISITATION	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	EX	EX	--	--
A148	CORRIDOR/ SALLY PORT	SFG	SHM	3'-0"	7'-0"	2"	--	SHM	--	--	--	--	--	SG1	DH-1.0	--	2
A149	CONFERENCE ROOM	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	EX	EX	--	--
A150	CLASSROOM	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	EX	EX	--	--
A151	CORRIDOR/ SALLY PORT	SFG	SHM	3'-0"	7'-0"	2"	F1	SHM	--	--	--	--	--	SG1	DH-2.0	--	1
AD1 - 5 PIPE SPACE ACCESS DOOR																	
AD1 - 5	PIPE SPACE ACCESS DOOR	F	SHM	2'-0"	6'-2"	2"	F1A	SHM	H4	J4	J4	1/2 HR.	--	--	DH-4.0	--	MOUNT 8" A.F.F.
FIRST FLOOR - AREA B																	
B106	TOILET ROOM	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4A	J4A	--	--	--	--	8B	3R	--
B109	HALL	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	4A	--	2
B109A	HALL	SFG	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H6	J6	S4	--	LEVEL 3	ISG1	4B	--	2
B110	ARMORY	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	LEVEL 3	--	4A	--	2
B111	VESTIBULE	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	9	3WL	--
B112	NURSING	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	8A	--	--
B113	WOMEN'S LOCKER ROOM	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H4	J4	--	--	--	--	9	3WL	--
B115	VESTIBULE	F	HM	3'-0"	7'-0"	1 3/4"	F1	HM	H5	J5	--	--	--	--	9	3ML	--
B116	MEN'S LOCKER ROOM	EX	HM	3'-0"	7'-0"	1 3/4"	EX	HM	--	--	--	--	--	--	EX	3ML	--

ABBREVIATIONS

EX EXISTING
GLZ GLAZING
HR HOUR
HM HOLLOW METAL
SHM SECURITY HOLLOW METAL
SIM SIMILAR
SISTL STAINLESS STEEL THICKNESS

GLAZING TYPES
GL1 - 1/4" TEMPERED CLEAR GLASS
SG1 - 3/4" SECURITY GLASS
SG2 - 1/8" FIRE RATED SECURITY GLASS (3/4 HR.)
SG3 - 2/8" FIRE RATED SECURITY GLASS (1-1/2 HR.)
BRG1 - 1/8" LEVEL 3 BULLET RESISTANT GLAZING
IGL1 - 1" INSULATED TEMPERED GLASS
ISG1 - 1-1/4" INSULATED SECURITY GLAZING (LEVEL 3 BULLET RESISTANT)

DOOR SCHEDULE GENERAL NOTES

A. PAINT ALL NEW HOLLOW METAL DOORS AND FRAMES.

B. PAINT EXISTING HOLLOW METAL DOORS AND FRAMES AT SIDE FACING ROOMS THAT ARE INDICATED ON THE ROOM FINISH SCHEDULE TO BE PAINTED.

C. COORDINATE DOORS REQUIRING UNDERCUT WITH HVAC CONTRACTOR.

D. ALL NEW HOLLOW METAL DOOR FRAMES TO HAVE SILENCERS.

E. PROVIDE MASTER KEYING PER OWNER'S DIRECTION.

F. LEVER HANDLE OR PUSH PLATE ACTIVATION HARDWARE TO BE INSTALLED ON ALL NEW NON-DETENTION DOORS. NEW HARDWARE MUST BE EASILY OPERATED WITH ONE HAND AND NOT REQUIRE TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST TO OPERATE.

DOOR SCHEDULE FOOTNOTES

1. ELECTRIC LOCK OPERATED BY CENTRAL BOOKING CONTROL AND PRISON CENTRAL CONTROL.

2. ELECTRIC LOCK OPERATED BY PRISON CENTRAL CONTROL.

3. CARD READER WITH REQUEST TO EXIT AT OPPOSITE SIDE OF DOOR.

4. CARD READER BOTH SIDES OF DOOR.

5. CARD AND FINGERPRINT READER AT CORRIDOR SIDE OF DOOR.

6. CARD AND FINGERPRINT READER AT CORRIDOR SIDE OF DOOR. CARD READER AT OPPOSITE SIDE OF DOOR.

SIGN TYPE NOTES:

A. SIGN TYPES ARE PROVIDED FOR GENERAL REFERENCE ONLY. ALL SIGNAGE SHALL COMPLY WITH ICC 2018 AND ICC A117.1 REQUIREMENTS.

B. ALL SIGNAGE SHALL HAVE A NON-GLARE FINISH. CHARACTERS AND PICTOGRAMS SHALL CONTRAST WITH BACKGROUND.

C. CHARACTERS SHALL BE UPPER CASE, SANS SERIF, ITALIC, OBLIQUE, SCRIPT OR DECORATIVE FONTS ARE NOT ACCEPTABLE.

D. VISUAL CHARACTERS SHALL BE 5/8" MIN IN HEIGHT, AND SHALL COMPLY WITH ICC A117.1-2009 TABLE 703.2.4. RAISED CHARACTERS SHALL BE 5/8" MIN AND 2" MAX. SPACING BETWEEN SEPARATE LINES OF CHARACTERS SHALL BE 1/8" MIN AND 1/5" MAX OF THE CHARACTER HEIGHT.

F. STROKE THICKNESS SHALL BE 10% MIN AND 30% MAX OF THE HEIGHT OF UPPER CASE "I" FOR VISUAL CHARACTERS, AND 15% MIN AND 30% MAX OF THE HEIGHT OF UPPER CASE "I" FOR RAISED CHARACTERS.

G. RAISED CHARACTERS SHALL BE 1/32" MIN ABOVE SIGN SURFACE.

H. BRAILLE, AND RAISED CHARACTERS SHALL BE SEPARATED 3/8" MIN FROM RAISED BORDERS, AND OTHER RAISED ELEMENTS.

J. BRAILLE DOTS SHALL BE ROUNDED OR DOMED.

K. PICTOGRAMS SHALL HAVE A FIELD 5" MIN IN HEIGHT. NO OTHER ELEMENTS ARE ALLOWED WITHIN REQUIRED FIELD.

RESTROOM
TYPE 3R
6" x 9"

MEN LOCKERS
TYPE 3ML
6" x 9"

WOMEN LOCKERS
TYPE 3WL
6" x 9"

EXIT
TYPE 12A
6" x 9"

NOTE: DIMENSIONS ARE TO BASELINE OF LOWEST AND HIGHEST TACTILE CHARACTER OR BRAILLE

VISUAL & RAISED CHARACTERS, BRAILLE, PICTOGRAM

YORK COUNTY CENTRAL BOOKING RELOCATION

3400 CONCORD ROAD
YORK, PA 17402
SPRINGFIELD TOWNSHIP, YORK COUNTY
YORK COUNTY BOARD OF COMMISSIONERS

REVISIONS
MARK ISSUED DATE DESCRIPTION

PROJECT NO: 77332-07
ISSUED DATE: 03/27/23
DRAWN BY: UJ, ALH
CHECKED BY: ALH
SHEET TITLE: 09 BUCHART HORN, INC.

DOOR SCHEDULE, DOOR AND FRAME TYPES AND DETAILS

ISSUED FOR BID

A-602