
SECTION 07 21 00
THERMAL INSULATION**PART 1 GENERAL****1.1 SECTION INCLUDES**

- A. Board insulation and integral vapor retarder at cavity wall construction, perimeter foundation wall, and underside of floor slabs.

1.2 RELATED REQUIREMENTS

- A. Section 07 21 29 - Sprayed Insulation: Sprayed-on, adhered closed cell polyurethane insulation.
- B. Section 07 25 00 - Weather Barriers: Separate weather barrier and vapor retarder materials.
- C. Section 09 21 16 - Gypsum Board Assemblies: Acoustic insulation inside walls and partitions.

1.3 REFERENCE STANDARDS

- A. ASTM C578 - Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation; 2015a.
- B. ASTM C1289 - Standard Specification for Faced Rigid Cellular Polyisocyanurate Thermal Insulation Board; 2014.

1.4 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data on product characteristics, performance criteria, and product limitations.

1.5 FIELD CONDITIONS

- A. Do not install insulation adhesives when temperature or weather conditions are detrimental to successful installation.

PART 2 PRODUCTS**2.1 MANUFACTURERS**

- A. Basis of Design Manufacturer - Thermal Insulation: Dow Chemical Company; www.dow.com or products meeting project requirements by one of the following:
 - 1. Hunter Panels: www.hunterpanels.com.
 - 2. Johns Manville: www.jm.com.
 - 3. Kingspan Insulation LLC: www.kingspan.com.
 - 4. Owens Corning Corporation: www.ocbuildingspec.com.

2.2 APPLICATIONS

- A. Insulation Under Concrete Slabs: Extruded polystyrene (XPS) board.
- B. Insulation at Perimeter of Foundation (Interior Face): Extruded polystyrene (XPS) board.
- C. Insulation on Inside of Concrete and Masonry Exterior Walls: Polyisocyanurate foam core board laminated between two aluminum facers.

2.3 FOAM BOARD INSULATION MATERIALS

- A. Extruded Polystyrene (XPS) Board Insulation - Under Slab: Complies with ASTM C578 with either natural skin or cut cell surfaces.
 - 1. Type and Compressive Resistance: Type IV, 25 psi (173 kPa), minimum.
 - 2. Board Edges: Square.

-
3. Basis of Design: Dow Chemical Company; STYROFOAM Brand Square Edge Insulation; www.dow.com.
 - B. Extruded Polystyrene (XPS) Board Insulation - Under Slab: Complies with ASTM C578 with either natural skin or cut cell surfaces.
 1. Type and Compressive Resistance: Type IV, 25 psi (173 kPa), minimum.
 2. Board Edges: Square.
 3. Basis of Design: Dow Chemical Company; STYROFOAM Brand Square Edge Insulation; www.dow.com or products meeting project requirements by one of the following:
 4. Manufacturers:
 - a. Kingspan Insulation LLC; GreenGuard XPS Type IV, 25 psi: www.kingspan.com/#sle.
 - b. Owens Corning Corporation; FOAMULAR Extruded Polystyrene (XPS) Insulation: www.ocbuildingspec.com/#sle.
 - C. Polyisocyanurate (ISO) Board Insulation: Rigid cellular foam, complying with ASTM C1289.
 1. Classifications:
 - a. Type I: Faced with aluminum foil on both major surfaces of the core foam.
 - 1) Class 2 - Glass fiber reinforced or non-reinforced core foam.
 - 2) Compressive Strength: 16 psi, minimum.
 - 3) Thermal Resistance, R-value: At 1-1/2 inch thick; 9.0 at 75 degrees F.
 2. Board Size: 48 inch by 96 inch.
 3. Board Thickness: 3.0 inch.
 4. Board Edges: Square.
 5. Basis of Design: Dow Chemical Company; THERMAXX XARMOR (ci); www.dow.com or comparable products meeting project requirements by one of the following:
 6. Manufacturers:
 - a. Atlas Roofing Corporation: www.atlasroofing.com.
 - b. Hunter Panels: www.hunterpanels.com.
 - c. Johns Manville: www.jm.com.

2.4 ACCESSORIES

- A. Tape: Reinforced polyethylene film with acrylic pressure sensitive adhesive.
 1. Application: Sealing of interior circular penetrations, such as pipes or cables.
 2. Width: As required for application.
 3. Temperature Resistance: Minus 40 degrees F to 212 degrees F
- B. Tape joints of rigid insulation in accordance with insulation manufacturers' instructions.
- C. Flashing and Sealant: Provide spray applied flashing and sealant component as recommended by board insulation manufacturer:
 1. Product: LiquidArmor -CM Flashing and Sealant by Dow.
- D. Adhesive: Type recommended by insulation manufacturer for application.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Verify that substrate, adjacent materials, and insulation materials are dry and that substrates are ready to receive insulation.

- B. Verify substrate surfaces are flat, free of honeycomb, fins, irregularities, or materials or substances that may impede adhesive bond.

3.2 BOARD INSTALLATION AT FOUNDATION PERIMETER

- A. Adhere a 6 inches wide strip of polyethylene sheet over construction, control, and expansion joints with double beads of adhesive each side of joint.
- B. Install boards horizontally on foundation perimeter.
- C. Cut and fit insulation tightly to protrusions or interruptions to the insulation plane.

3.3 BOARD INSTALLATION AT CAVITY WALLS

- A. Secure impale fasteners to substrate at following frequency:
 - 1. Six (6) per insulation board or as required by insulation board manufacturer.
- B. Install boards to fit snugly between wall ties.
- C. Install boards horizontally on walls.
- D. Cut and fit insulation tightly to protrusions or interruptions to the insulation plane.

3.4 BOARD INSTALLATION UNDER CONCRETE SLABS

- A. Place insulation under slabs on grade after base for slab has been compacted.
- B. Cut and fit insulation tightly to protrusions or interruptions to the insulation plane.
- C. Prevent insulation from being displaced or damaged while placing vapor retarder and placing slab.

3.5 PROTECTION

- A. Do not permit installed insulation to be damaged prior to its concealment.

END OF SECTION 07 21 00