
SECTION 09 51 00
ACOUSTICAL CEILINGS

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Suspended metal grid ceiling system.
- B. Acoustical units.

1.2 RELATED REQUIREMENTS

- A. Section 05 31 00 - Steel Decking: Placement of special anchors or inserts for suspension system.

1.3 REFERENCE STANDARDS

- A. ASTM C635/C635M - Standard Specification for Manufacture, Performance, and Testing of Metal Suspension Systems for Acoustical Tile and Lay-in Panel Ceilings 2022.
- B. ASTM C636/C636M - Standard Practice for Installation of Metal Ceiling Suspension Systems for Acoustical Tile and Lay-In Panels 2019.
- C. ASTM E580/E580M - Standard Practice for Installation of Ceiling Suspension Systems for Acoustical Tile and Lay-in Panels in Areas Subject to Earthquake Ground Motions 2022.
- D. ASTM E1264 - Standard Classification for Acoustical Ceiling Products 2022.

1.4 ADMINISTRATIVE REQUIREMENTS

- A. Sequence work to ensure acoustical ceilings are not installed until building is enclosed, sufficient heat is provided, dust generating activities have terminated, and overhead work is completed, tested, and approved.
- B. Do not install acoustical units until after interior wet work is dry.

1.5 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements for submittal procedures.
- B. Shop Drawings: Indicate grid layout and related dimensioning.
- C. Product Data: Provide data on suspension system components and acoustical units.
- D. Samples: Submit two samples, minimum 4 by 4 inch in size illustrating material and finish of acoustical units.
- E. Samples: Submit two samples each, minimum 4 inches long, of suspension system main runner, cross runner, and perimeter molding.
- F. Manufacturer's Installation Instructions: Indicate special procedures and perimeter conditions requiring special attention.
- G. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.
 - 1. See Section 01 60 00 - Product Requirements, for additional provisions.
 - 2. Extra Acoustical Units: Quantity equal to 5 percent of total installed.

1.6 QUALITY ASSURANCE

- A. Suspension System Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years documented experience.
- B. Acoustical Unit Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years documented experience.

1.7 FIELD CONDITIONS

- A. Maintain uniform temperature of minimum 60 degrees F, and maximum humidity of 40 percent prior to, during, and after acoustical unit installation.

PART 2 PRODUCTS**2.1 MANUFACTURERS**

- A. Basis of Design Manufacturer - Acoustic Tiles/Panels:
1. Armstrong World Industries, Inc; Optima: www.armstrongceilings.com/#sle.
 2. Other acceptable manufacturers: Provide products meeting project requirements by one of the following:
 - a. CertainTeed Corporation: www.certainteed.com/#sle.
 - b. USG Corporation: www.usg.com/ceilings/#sle.
- B. Basis of Design Manufacturer - Suspension Systems:
1. Armstrong World Industries, Inc; Prelude XL: www.armstrongceilings.com/#sle.
 2. Other acceptable manufacturers: Provide products meeting project requirements by one of the following:
 - a. CertainTeed Corporation: www.certainteed.com/#sle.
 - b. USG Corporation: www.usg.com/ceilings/#sle.

2.2 ACOUSTICAL UNITS

- A. Acoustical Units - General: ASTM E1264, Class A.
- B. Acoustical Panels, Type ACT-1: Mineral fiber with membrane-faced overlay, with the following characteristics:
1. Classification: ASTM E1264 Type IV.
 - a. Form: 2, water felted.
 - b. Pattern: "E" - lightly textured.
 2. Size: 24 by 48 inch.
 3. Thickness: 3/4 inch.
 4. Light Reflectance: 0.88 percent, determined in accordance with ASTM E1264.
 5. NRC Range: 0.75, determined in accordance with ASTM E1264.
 6. Ceiling Attenuation Class (CAC): 35, determined in accordance with ASTM E1264.
 7. Panel Edge: Square.
 8. Suspension System: Exposed grid.
 9. Products:
 - a. Armstrong World Industries, Inc; Ultima: www.armstrongceilings.com/#sle.
- C. Acoustical Panels, Type ACT-2: Glass fiber with membrane-faced overlay, with the following characteristics:
1. Classification: ASTM E1264 Type XII.
 - a. Form: 2, cloth.
 - b. Pattern: "E" - lightly textured.
 2. Size: 24 by 48 inch.
 3. Thickness: 3/4 inch.
 4. Light Reflectance: 0.88 percent, determined in accordance with ASTM E1264.
 5. NRC Range: 90 to 95, determined in accordance with ASTM E1264.
-

6. Articulation Class (AC): 180, determined in accordance with ASTM E1264.
7. Panel Edge: Square.
8. Color: White.
9. Suspension System: Exposed grid.
10. Basis of Design Product:
 - a. Armstrong World Industries, Inc; Optima: www.armstrongceilings.com/#sle.

2.3 SUSPENSION SYSTEM(S)

- A. Metal Suspension Systems - General: Complying with ASTM C635/C635M; die cut and interlocking components, with perimeter moldings, hold down clips, stabilizer bars, clips, and splices as required.
- B. Metal Suspension Systems - General: Complying with ASTM C635/C635M; die cut and interlocking components, with perimeter moldings, hold down clips, stabilizer bars, clips, and splices as required.
- C. Exposed Suspension System: Hot-dipped galvanized steel grid with aluminum cap.
 1. Structural Classification: Intermediate-duty, when tested in accordance with ASTM C635/C635M.
 2. Profile: Tee; 15/16 inch face width.
 3. Finish: Baked enamel.
 4. Color: White.
 5. Basis of Design Product:
 - a. Armstrong World Industries, Inc; Prelude XL: www.armstrongceilings.com/#sle.

2.4 ACCESSORIES

- A. Support Channels and Hangers: Galvanized steel; size and type to suit application, seismic requirements, and ceiling system flatness requirement specified.
- B. Hanger Wire: 12 gauge, 0.08 inch galvanized steel wire.
- C. Hold-Down Clips: Manufacturer's standard clips to suit application.
- D. Perimeter Moldings: Same metal and finish as grid.
 1. Size: As required for installation conditions.
 2. Angle Molding: L-shaped, for mounting at same elevation as face of grid.
- E. Touch-up Paint: Type and color to match acoustical and grid units.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Verify existing conditions before starting work.
- B. Verify that layout of hangers will not interfere with other work.

3.2 PREPARATION

- A. Install after major above-ceiling work is complete.
- B. Coordinate the location of hangers with other work.
- C. Provide hanger clips during steel deck erection. Provide additional hangers and inserts as required.

3.3 INSTALLATION - SUSPENSION SYSTEM

- A. Install suspension system in accordance with ASTM C636/C636M, ASTM E580/E580M, and manufacturer's instructions and as supplemented in this section.
- B. Rigidly secure system, including integral mechanical and electrical components, for maximum deflection of 1:360.

-
- C. Lay out system to a balanced grid design with edge units no less than 50 percent of acoustical unit size.
 - D. Perimeter Molding: Install at intersection of ceiling and vertical surfaces and at junctions with other interruptions.
 - 1. Use longest practical lengths.
 - E. Suspension System, Non-Seismic: Hang suspension system independent of walls, columns, ducts, pipes and conduit. Where carrying members are spliced, avoid visible displacement of face plane of adjacent members.
 - F. Where ducts or other equipment prevent the regular spacing of hangers, reinforce the nearest affected hangers and related carrying channels to span the extra distance.
 - G. Do not support components on main runners or cross runners if weight causes total dead load to exceed deflection capability.
 - H. Support fixture loads using supplementary hangers located within 6 inches of each corner, or support components independently.
 - I. Do not eccentrically load system or induce rotation of runners.

3.4 INSTALLATION - ACOUSTICAL UNITS

- A. Install acoustical units in accordance with manufacturer's instructions.
- B. Fit acoustical units in place, free from damaged edges or other defects detrimental to appearance and function.
- C. Fit border trim neatly against abutting surfaces.
- D. Install acoustical units level, in uniform plane, and free from twist, warp, and dents.
- E. Cutting Acoustical Units:
 - 1. Make field cut edges of same profile as factory edges.
- F. Install hold-down clips on panels within 20 ft of an exterior door.

3.5 TOLERANCES

- A. Maximum Variation from Flat and Level Surface: 1/8 inch in 10 feet.
- B. Maximum Variation from Plumb of Grid Members Caused by Eccentric Loads: 2 degrees.

END OF SECTION 09 51 00