



LIGHTING FIXTURE SCHEDULE							
DESIGNATION	DESCRIPTION	LAMPS	VOLTAGE/ DRIVER	MOUNTING	MANUFACTURER	CATALOG NUMBER	REMARKS
A	1'-0" X 4'-0" X 1.88"D SURFACE LED SECURITY FIXTURE WITH 14GA STEEL FRAME AND .25"TH CLEAR POLYCARBONATE LENS	40W LED 3800 LUMENS 4200K, 80 CRI	REMOTE UNIVERSAL 10-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	AGM-14-UN-42 FMS-X12-4-LD4-1STD-40-UNV-80/96-EDD1 SCA-4-0/3-45L40K-DCC-DV-6/9-1	
Ae	1'-0" X 4'-0" X 1.88"D SURFACE LED SECURITY FIXTURE WITH 14GA STEEL FRAME AND .25"TH CLEAR POLYCARBONATE LENS	40W LED 3800 LUMENS 4200K, 80 CRI	REMOTE UNIVERSAL 10-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	AGM-14-UN-42-EL FMS-X12-4-LD4-1STD-40-UNV-80/96-EDD1-EL14W SCA-4-0/3-45L40K-DCC-DV-6/9-1-EM "REMOTE BATTERY"	PROVIDED WITH REMOTE BATTERY PACK
B	1'-0" X 1'-0" X 1.88"D SURFACE LED SECURITY FIXTURE WITH 14GA STEEL FRAME AND .25"TH CLEAR POLYCARBONATE LENS	18W LED 1400 LUMENS 4200K, 80 CRI	REMOTE UNIVERSAL 10-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	AGM-11-UN-42 FW-LD2-1212-1700-40-UNV-CP25-R4-EDD1 SQCA-0/3-23L40K-DCC-DV-6/9-1	
Be	1'-0" X 1'-0" X 1.88"D SURFACE LED SECURITY FIXTURE WITH 14GA STEEL FRAME AND .25"TH CLEAR POLYCARBONATE LENS	18W LED 1400 LUMENS 4200K, 80 CRI	REMOTE UNIVERSAL 10-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	AGM-11-UN-42-EL FW-LD2-1212-1700-40-UNV-CP25-R4-EDD1-EL7W SQCA-0/3-23L40K-DCC-DV-6/9-1-EM "REMOTE BATTERY"	PROVIDED WITH REMOTE BATTERY PACK
C	1'-0" X 4'-0" X 5"D SURFACE LED SECURITY FIXTURE WITH 16GA STEEL HOUSING AND .187"TH CLEAR POLYCARBONATE OUTER/.125TH PRISMATIC ACRYLIC INNER LENS	50W LED 6000 LUMENS 4000K, 80 CRI	UNIVERSAL 1-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	5314-C-L2-40-1C-1-A-UN FMS-X12-4-LD4-2STD-40-UNV-80/94-EDD1 SDA-4-1/3-67L40K-DCC-DV-1/7-1	
Ce	1'-0" X 4'-0" X 5"D SURFACE LED SECURITY FIXTURE WITH 16GA STEEL HOUSING AND .187"TH CLEAR POLYCARBONATE OUTER/.125TH PRISMATIC ACRYLIC INNER LENS	50W LED 6000 LUMENS 4000K, 80 CRI	UNIVERSAL 1-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	5314-C-L2-40-1C-1-A-UN-EL1 FMS-X12-4-LD4-2STD-40-UNV-80/94-EDD1-EL14W SDA-4-1/3-67L40K-DCC-DV-1/7-1-EM "REMOTE BATTERY"	PROVIDED WITH INTEGRAL BATTERY PACK, 1250 LUMENS
D	12.5" X 12.5" X 4.25"D SURFACE LED HIGH ABUSE FIXTURE WITH BRONZE FINISH	17W LED 2347 LUMENS 4000K, 80 CRI	UNIVERSAL 10-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	GWSO-DM40-UN-BZ G12-PP-BZ-LD4-30W-40-OPL-UNV-EDD1 MS11FL-PP-DB-20L40K-DV	
De	12.5" X 12.5" X 4.25"D SURFACE LED HIGH ABUSE FIXTURE WITH BRONZE FINISH	17W LED 2347 LUMENS 4000K, 80 CRI	UNIVERSAL 10-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	GWSO-DM40-UN-BZ G12-PP-BZ-LD4-30W-40-OPL-UNV-EDD1-EL5W/CTSG/BZ MS11FL-PP-DB-20L40K-DV-L-EL-SA	PROVIDED WITH INTEGRAL BATTERY PACK
E	5.27"W X 4'-0"L X 4"D PENDANT LED LINEAR FIXTURE WITH WIDE DIFFUSE LENS AND WHITE FINISH	28W LED 4000 LUMENS 4000K, 80 CRI	UNIVERSAL 10-100% 0-10V DIMMING	PENDANT CABLE	LITHONIA FAIL-SAFE HE WILLIAMS	CLX-L48-SEF-WDL-MVOLT-GZ10-40K-80CRI-WH 4SNX-45SL-SLW-UNV-L840-CD1-U 76R-4-L52/840-(L40)-DIM-UNV	
Fe	12.5" X 12.5" X 4.25"D WALL SURFACE LED HIGH ABUSE FIXTURE WITH BRONZE FINISH AND CUT-OFF FRAME	17W LED 2347 LUMENS 4000K, 80 CRI	UNIVERSAL 10-100% 0-10V DIMMING	WALL SURFACE ABOVE DOOR	NEW STAR LIGHTING FAIL-SAFE KENALL	GWSC-MD-40-UN-BZ-EL G12-E-BZ-LD4-30W-40-OPL-UNV-EDD1-EL5W-CTSG/Z MS11EL-PP-DB-20L40K-DV-L-EL-SA	PROVIDED WITH INTEGRAL BATTERY PACK
Ge	1'-0"L X 2'-0"L X 5"D SURFACE LED SECURITY FIXTURE WITH 16GA STEEL HOUSING AND .187"TH CLEAR POLYCARBONATE OUTER/.125TH PRISMATIC ACRYLIC INNER LENS	25W LED 3000 LUMENS 4000K, 80 CRI	UNIVERSAL 1-100% 0-10V DIMMING	SURFACE	NEW STAR LIGHTING FAIL-SAFE KENALL	5312-C-L2-40-1C-1-A-UN-EL1 FMS-D-12-2-LD4-2STD-40-UNV-80/94-EDD1-EL10W SDA-2-1/3-45L40K-DCC-DV-1/7-1	PROVIDED WITH INTEGRAL BATTERY PACK, 1250 LUMENS
H	5.27"W X 4'-0"L X 4"D SURFACE LED LINEAR FIXTURE WITH ROUND DIFFUSE LENS AND WHITE FINISH	28W LED 4000 LUMENS 4000K, 80 CRI	UNIVERSAL 10-100% 0-10V DIMMING	SURAFCE	LITHONIA METALLUX HE WILLIAMS	THCLX-L48-SEF-RDL-MVOLT-GZ10-40K-80CRI-WH 4SNX-45SL-LW-UNV-L840-CD1-U 76R-4-L52/835-(L48)-DIM-UNV	
J	3'-0"L LED UNDERCABINET LIGHT WITH WHITE MATTE FINISH, INTEGRAL ROCKER SWITCH AND OCCUPANCY SENSOR	16W LED 1800 LUMENS 4000K, 80 CRI	120V ELECTRONIC DRIVER	SURFACE UNDERCABINET	HE WILLIAMS FAIL-SAFE	1SF-3-L18/840-AF12125-WRS/120-OCCLV OSF10-10W-DRV-120 UCL-3-LD4-40-A12125-EDD1-UNV-OS-RSW	
K	2'-0" CORRECTIONAL WALL-MOUNTED LED FIXTURE WITH .125 PRISMATIC/.125 CLEAR POLYCARBONATE INNER/OUTER LENS 14 GA HOUSING AND T20 CENTER PIN TAMPERPROOF TORX SCREWS	31W LED 2150 LUMNES 4000K, 80 CRI	UNIVERSAL ELECTRONIC NON-DIMMING	WALL ABOVE MIRROR	FAIL-SAFE KENALL NEW STAR LIGHTING	FMB-X-2-LD4-1LO-40-UNV-80/84-EDC1 WCU-2-0/3-1/1-25L40K-DCC-DV-6/9-1 RUD2-B-LA401C-A/A-UN-DM	WHITE FINISH
L	12.5" X 12.5" X 4.25"D WALL SURFACE LED HIGH ABUSE FIXTURE WITH BRONZE FINISH AND CUT-OFF FRAME	25W LED 3223 LUMENS 4000K, 80 CRI	UNIVERSAL 10-100% 0-10V DIMMING	WALL SURFACE AT EXISTING LOCATION	NEW STAR LIGHTING FAIL-SAFE KENALL	GWSC-HG-40-UN-BZ G12-E-BZ-LD4-30W-40-OPL-UNV-EDD1-CTSG/Z MS11EL-PP-DB-30L40K-DV-SA	
EM	LED EMERGENCY LIGHTING UNIT	TWO (2) 1.9W LED	120/277V	WALL 7'-6" AFF	LITHONIA EXITRONIX HE WILLIAMS	WLTU LED LED-RX-2 EMER/W-GRAY-D	
EX	LED SECURITY SINGLE FACE EXIT SIGN WITH RED LETTERS, WHITE FINISH EMERGENCY BATTERY PACK AND TORX HEAD W/ CENTER PIN FASTENERS	LED	120/277V	WALL BACK ABOVE DOOR	KENALL EXITRONIX NEW STAR LIGHTING	MMEX-1-0-R-DT-1-EL EXL-7-1-RW-XX 620-SF-LED-UN-RW-EM	
EX2	LED SECURITY DOUBLE FACE EXIT SIGN WITH RED LETTERS, WHITE FINISH EMERGENCY BATTERY PACK AND TORX HEAD W/ CENTER PIN FASTENERS	LED	120/277V	TOP MOUNT	KENALL EXITRONIX NEW STAR LIGHTING	MMEX-2-0-R-DT-1-EL EXL-7-2-RW-XX 620-DF-LED-UN-RW-EM	
NL	4.25"H X 10.35"L 3.8"D LED NIGHT LIGHT WITH MATTE WHITE FINISH, CLEAR POLCARBONATE LENS AND TORX HEAD W/ CENTER PIN FASTENERS	LED .5W	120V ELECTRONIC	WALL 18" AFF	KENALL FAIL-SAFE NEW STAR LIGHTING	MSL-L-0-MW-CP-WLL-120-2-BH MHN-UNV-W-TP SWL3-OF-L-32-12-W-TH	

REMARKS

1. THE 4 IS RESPONSIBLE FOR ALL LIGHTING, MOUNTING ACCESSORIES, POWER SUPPLIES AND MISC PIECES TO INSURE A COMPLETE INSTALLATION. REFER TO FLOOR PLANS FOR LOCATION AND LENGTH OF RUNS.

RECORD REVISIONS		
<div></div>		
PROFESSIONAL'S SIGNATURE DATE		
<div><div>UpStreet ARCHITECTS, INC.</div><div>541 PHILADELPHIA ST. 911 MENOHER BLVD. INDIANA, PA 15701 JOHNSTOWN, PA 15905</div></div>		
COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF GENERAL SERVICES HARRISBURG, PENNSYLVANIA		
D.G.S. PROJECT No. C-0588-0015 PHASE 1		
LOYSVILLE YOUTH DEVELOPMENT CENTER- RENOVATIONS TO ZIMMERMAN- BINGAMAN (ZB) COTTAGE DEPARTMENT OF HUMAN SERVICES LOYSVILLE, TYRONE TOWNSHIP, PERRY COUNTY, PA		
SCHEDULES - ELECTRICAL		
VERIFY SCALE		
BAR IS ONE (1) INCH LONG ON ORIGINAL DRAWING: <div>0  1</div>		
IF BAR IS NOT ONE (1) INCH LONG, ADJUST SCALE ACCORDINGLY		
CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS. VARIANCE FROM CONTRACT DOCUMENTS NOT PERMITTED WITHOUT PROFESSIONAL & BUREAU OF CONSTRUCTION APPROVAL.	DRAWN BY S. SMOLKO CHECKED BY S. MULHOLLEN	DATE 27 JUNE 2023 SCALE AS NOTED
SHEET No. E-703		