

SECTION 102800
TOILET AND BATH ACCESSORIES

PART 1 GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following:

- 1. Public-use washroom accessories.
- 2. Underlavatory guards.

1.3 SUBMITTALS

- A. Product Data: For each type of product indicated. Include the following:

- 1. Construction details and dimensions.
- 2. Anchoring and mounting requirements, including requirements for cutouts in other work and substrate preparation.
- 3. Material and finish descriptions.
- 4. Features that will be included for Project.
- 5. Manufacturer's warranty.

- B. Product Schedule: Indicating types, quantities, sizes, and installation locations by room of each accessory required.

- 1. Identify locations using room designations indicated on Drawing A.1.1 and A.3.1.
- 2. Identify products using designations indicated on Drawing A.3.1.

- C. Maintenance Data: For toilet and bath accessories to include in maintenance manuals.

1.4 QUALITY ASSURANCE

- A. Source Limitations: For products listed together in the same articles in Part 2, provide products of same manufacturer unless otherwise approved by Government Design Professional.

1.5 COORDINATION

- A. Coordinate accessory locations with other work to prevent interference with clearances required for access by people with disabilities, and for proper installation, adjustment, operation, cleaning, and servicing of accessories.

- B. Deliver inserts and anchoring devices set into concrete or masonry as required to prevent delaying the Work.

1.6 WARRANTY

- A. Special Mirror Warranty: Manufacturer's standard form in which manufacturer agrees to replace mirrors that develop visible silver spoilage defects and that fail in materials or workmanship within specified warranty period.
 - 1. Warranty Period: 15 years from date of Substantial Completion.

PART 2 PRODUCTS

2.1 MATERIALS

- A. Stainless Steel: ASTM A 666, Type 304, 0.0312-inch minimum nominal thickness, unless otherwise indicated.
- B. Brass: ASTM B 19 flat products; ASTM B 16, rods, shapes, forgings, and flat products with finished edges; or ASTM B 30, castings.
- C. Steel Sheet: ASTM A 1008/A 1008M, Designation CS (cold rolled, commercial steel), 0.0359-inch minimum nominal thickness.
- D. Galvanized Steel Sheet: ASTM A 653/A 653M, with G60 hot-dip zinc coating.
- E. Galvanized Steel Mounting Devices: ASTM A 153/A 153M, hot-dip galvanized after fabrication.
- F. Fasteners: Screws, bolts, and other devices of same material as accessory unit and tamper-and-theft resistant where exposed, and of galvanized steel where concealed.
- G. Chrome Plating: ASTM B 456, Service Condition Number SC 2 (moderate service).
- H. Mirrors: ASTM C 1503, Mirror Glazing Quality, clear-glass mirrors, nominal 6.0 mm thick.
- I. ABS Plastic: Acrylonitrile-butadiene-styrene resin formulation.

2.2 PUBLIC-USE WASHROOM ACCESSORIES

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - 1. Kimberly-Clark Professional (Government Preferred)
 - 2. AFIA Skin Care Solutions (Government Preferred)
 - 3. "Or Approved Equal"
- B. Toilet Tissue (Roll) Dispenser (KC Model: 09551)
 - 1. Description: Cored JRT toilet paper dispenser.
 - 2. Mounting: Surface mounted.
 - 3. Operation: Manual dispensing.

4. Capacity: (2) 9.38" dia. rolls [or] (1) 13" dia roll.
5. Material and Finish: ABS Plastic in Smoke Grey.

C. Paper Towel (Roll) Dispenser (KC Model: 09765)

1. Description: Lever-actuated mechanism permits controlled delivery of paper rolls in preset lengths per stroke.
2. Mounting: Surface mounted.
3. Capacity: 8-inch wide with 1.5" core
4. Material and Finish: ABS plastic, Smoke Grey.
5. Lockset: Key Activated

D. Liquid-Soap Dispenser (AFIA Model: 4217)

1. Description: Push valve that dispenses soap in foam form.
2. Mounting: Vertically oriented, surface mounted.
3. Capacity: 1000ml or 1250ml (1 pack).
4. Lockset: Keyless lock.
5. Refill Indicator: Window type.
6. Lockset: Keyed Access

E. Grab Bars:

1. Mounting: Flanges with concealed fasteners.
2. Material: Stainless steel, 0.05 inch thick.
 - a. Finish: Smooth, No. 4, satin finish.
3. Outside Diameter: 1-1/2 inches.
4. Configuration and Length: Per Drawings and/or Chapter 6 of the ICC A117.1-2017.

F. Mirror Unit (American Specialties Model: 0600)

1. Frame: Stainless-steel angle, 0.05 inch thick.
 - a. Corners: Manufacturer's standard.
2. Hangers: Produce rigid, tamper- and theft-resistant installation, using method indicated below.
 - a. One-piece, galvanized steel, wall-hanger device with spring-action locking mechanism to hold mirror unit in position with no exposed screws or bolts.
 - b. Wall bracket of galvanized steel, equipped with concealed locking devices requiring a special tool to remove.
3. Size: 18" wide x 30" high or As indicated on Drawings.

2.3 FABRICATION

- A. General: Fabricate units with tight seams and joints, and exposed edges rolled. Hang doors and access panels with full-length, continuous hinges. Equip units for concealed anchorage and with corrosion-resistant backing plates.

- B. Keys: Provide universal keys for internal access to accessories for servicing and resupplying. Provide minimum of **three (3)** keys to Government Project Manager.

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install accessories according to manufacturers' written instructions, using fasteners appropriate to substrate indicated and recommended by unit manufacturer. Install units level, plumb, and firmly anchored in locations and at heights indicated.

3.2 ADJUSTING AND CLEANING

- A. Adjust accessories for unencumbered, smooth operation. Replace damaged or defective items.
- B. Remove temporary labels and protective coatings.
- C. Clean and polish exposed surfaces according to manufacturer's written recommendations.

END OF SECTION 102800