


### BUILDING CODE INFORMATION



1017 - EXIT ACCESS TRAVEL DISTANCE WITHOUT SPRINKLER:  
STORAGE: 300 FEET  
BUSINESS: 200 FEET

Diagram illustrating the placement of restroom signs relative to a door. The signs shown are:

- TYPICAL UNISEX SIGN
- TYPICAL WOMEN'S SIGN
- TYPICAL MEN'S SIGN
- TYPICAL EXIT SIGN

Dimensions and placement requirements:

- Sign height: 6'0" MAX
- Clearance from door handle: 3" MIN
- Clearance from door edge: 18" MIN
- Clearance from baseline of door: 48" MIN to 60" MAX

CLIMATE ZONE - CUMBERLAND COUNTY, ZONE 5A		REQUIRED	PROVIDED
ROOF	LOW: ATTIC + OTHER	R-38	R-38
WALLS ABOVE GRADE	MASS	R-14ci	R-12.5
	WOOD FRAMED AND OTHER	R-13 + R-38ci OR R-20	R-20
WALLS BELOW GRADE	BELOW GRADE WALL	R-15 ci	NA
SLAB-ON-GRADE FLOORS	UNHEATED SLABS	R-10 for 24" BELOW	R-10 FOR 24"
OPAQUE DOORS	NONSWINGING	R-4.75	R-13.5

BUILDING CODE INFORMATION

# A001