

## **Section 10 – BITUMINOUS PAVING**

### **A. DESCRIPTION**

This work shall be the placement of PENNDOT No. 2A stone subbase, Bituminous Concrete Base Course, Bituminous Concrete Binder Course and Bituminous Wearing Course to the limits indicated on the Contract Plans and described herein. This work shall include the furnishing and/or installation of all materials, equipment, and appurtenances and any other necessary work required for proper construction.

This work shall be in accordance with all applicable sections of PENNDOT Publication 408. The Contractor shall comply with all of the requirements of the Owner, PENNDOT, and other governmental agencies having jurisdiction over any phase of the work.

### **B. MATERIALS**

All materials shall be in accordance with the applicable sections of PENNDOT Publication 408, latest edition.

a. Subbase

PENNDOT No. 2A Stone in accordance with PENNDOT Publication 408.

b. Bituminous Concrete Base Course

Superpave HMA, 25mm PG 64-22, 0.3 to <3M ESAL's, in accordance with PENNDOT Publication 408.

c. Bituminous Binder Course

Superpave HMA, 9.5mm PG 64-22, 0.3 to <3M ESAL's, in accordance with PENNDOT Publication 408.

d. Bituminous Wearing Course:

Superpave HMA, 9.5mm PG 64-22, 0.3 to <3M ESAL's in accordance with PENNDOT Publication 408.

### **C. CONSTRUCTION**

This work shall be in accordance with all applicable sections of PENNDOT Publication 408.

END OF SECTION