

3 ALLEN STREET, SUITE 115  
STATE COLLEGE, PA 16801  
PHONE: 814-206-0981  
EMAIL: [achilde@wntf-inc.com](mailto:achilde@wntf-inc.com)  
[www.wntf-inc.com](http://www.wntf-inc.com)

&amp;W

N FRONT STREET, SUITE 200  
RISBURG, PA 17110  
TEL: 717-635-2835  
E-MAIL: mkurowski@kandwengineers.com  
www.kandwengineers.com


INNOVATION BLVD, SUITE 112  
TE COLLEGE, PA 19033  
NE: 814-237-2160  
AL: ras@ba-inc.com  
.ba-inc.com

PENN STREET, SUITE 104  
LIDAYSBURG, PA 16648  
PHONE: 814-317-5037  
EMAIL: [rdlwinney@DAStructures.com](mailto:rdlwinney@DAStructures.com)  
[www.DAStructures.com](http://www.DAStructures.com)

KEY PLAN:

SU BUILDING NUMBER: 0985095  
SU PROJECT NUMBER: 00-08713.00

DRAWING NO.



- 1 EXISTING IN-GRADE ELECTRICAL PULL BOX FOR POWER CIRCUITS.
- 2 EXISTING FIELD LIGHTING AND POWER CIRCUITS TO REMAIN.
- 3 COORDINATE ROUTING WITH INSTALLATION OF SANITARY SEWER. COORDINATE DEPTH OF  
DUCTBANK WITH SITE ENGINEER TO ALLOW FOR REQUIRED CLEARANCES FROM PIPING.  
INSTALL ALL UNDERGROUND PIPING AND DUCTBANK IN COMMON TRENCH.
- 4 EXTEND CONDUITS UP ABOVE GRADE TO IT CABINET IN PRESS BOX ABOVE. COORDINATE  
ELECTRICAL ROUTING IN FIELD. SECURE CONDUITS TO PRESS BOX STRUCTURAL STEEL.
- 5 FURNISH AND INSTALL 2#6, 8#6, 1" FOR RE-ROUTED SITE RECEPTACLE CIRCUIT. FURNISH  
AND INSTALL, (2) SETS OF 3#6, 3#8, #6, 1-1/2" FOR FIELD LIGHTING POLE CIRCUITS. VERIFY  
ACTUAL WIRING AND CONDUIT SIZES BEFORE INSTALLATION.
- 6 CAREFULLY EXCAVATE AND BACKFILL CONDUIT TRENCHES WHEN NEAR AND/OR CROSSING  
EXISTING UNDERGROUND PIPING AND CONDUITS. HAND EXCAVATE ONLY IN THIS AREA.  
REFER TO CIVIL DRAWINGS FOR ADDITIONAL INFORMATION.
- 7 LOCATE CUTTER 3'-0" FROM EDGE OF POLE BASE. VERIFY EXACT LOCATION WITH ARCHITECT  
AND UNIVERSITY BEFORE ROUGHEN. FIXTURE OUTLET BOX OR CONDUIT STUB-UP TO BE  
ANCHORED TO EXPANDED POLE BASE FOUNDATION. COORDINATE INSTALLATION WITH GC  
BEFORE ROUGHEN.
- 8 CONNECT WIRING FOR LIGHTING FIXTURE TO LOAD SIDE OF DISCONNECT SWITCH FOR  
SCOREBOARD (CUT, RP-13). FURNISH AND INSTALL 2#10, #10/3, 3/4" 3" FROM DISCONNECT,  
THROUGH PHOTOCELL LOCATED ON REAR OF SCOREBOARD, TO SCOREBOARD'S  
SUPPORTING COLUMN. THEN TO BELOW GRADE TO FIXTURE. PROVIDE SUPPORTING  
HARDWARE AS REQUIRED.
- 9 MOUNT TO TOP SIDE OF EXISTING EQUIPMENT CABINET AS DIRECTED BY UNIVERSITY.  
PROVIDE ACCESSORY SUPPORT BRACKETS AND/OR STRUCTURAL STEEL AS REQUIRED.  
COORDINATE ELECTRICAL LOCATION WITH UNIVERSITY.
- 10 RAISE JUNCTION BOX SO THAT THE TOP OF THE BOX IS LEVEL WITH FINAL SIDEWALK  
ELEVATION. FURNISH AND INSTALL ADDITIONAL MAINPANELS WITH COLLARS AS REQUIRED.

- 17 FURNISH AND INSTALL CAT 6 EXTENDED DISTANCE DATA CABLE IN EXISTING CONDUIT FOR  
OUTER WIRELESS ACCESS POINT. TERMINATE CABLE IN CAT CABINET IN PRESS BOX. REFER TO  
NOTE 18 FOR ADDITIONAL INFORMATION. ALSO FURNISH AND INSTALL CONTROL CABLES FOR  
SCORABOARD AND INFO BOARD CONTROL. RUN CABLE TO CONTROL LOCATIONS IN  
PRESS BOX. WIRING SHALL BE AS DIRECTED BY EQUIPMENT VENDORS.
- 12 REMOVE EXISTING POLE FIXTURE. REMOVE EXISTING ASSOCIATED POLE FOUNDATION AND  
WIRING. REMOVE EXISTING ASSOCIATED UNDERGROUND CONDUIT AS REQUIRED FOR  
CONSTRUCTION OF PARKING LOT. ABANDON REMAINDER.
- 13 REMOVE EXISTING ABANDONED PORT OF WIRING AND CONDUITS AFTER CIRCUITS AND  
CONDUITS ARE RE-ROUTED.
- 14 ADJUST TOP OF PULL BOX AS REQUIRED SO THAT TOP OF BOX IS LEVEL WITH FINAL GRADE  
ELEVATION. TRIM EXISTING BOX OR ADD MANUFACTURER'S COLLARS AS REQUIRED.
- 15 MOUNT LIGHTING FIXTURE FOR BLEACHERS AT MOUNTING HEIGHT INDICATED. CONNECT TO  
EXISTING BLEACHER LIGHTING CIRCUIT IN POLE. COORDINATE EXACT LOCATION AND  
INTERCEPTION ON POLE WITH FIELD LIGHTING SYSTEM MANUFACTURER.
- 16 OPERIENT EXISTING FIELD LIGHTING AND SITE POWER CONDUITS AT PULL BOX. SPLICE  
CIRCUITS AND EXTEND AS NOTED. EXTEND 2" CONDUITS FOR POWER TO REST ROOMS AND  
PRESS BOX AS INDICATED.
- 17 REMOVE EXISTING POLE FIXTURE AND EXISTING ASSOCIATED FOUNDATION. REMOVE  
EXISTING WIRING BACK TO SAFE POINT. INSTALL REPLACEMENT POLE FIXTURE INDICATED  
AND CONNECT TO EXISTING LIGHTING CIRCUIT.
- 18 FURNISH AND INSTALL CAT 6 EXTENDED DISTANCE DATA CABLE FROM CAMERA OUTLET,  
DOWN POLE AND THROUGH UNDERGROUND CONDUIT SYSTEM AND COMMUNICATIONS  
HANDHOLES. TO CAT CABINET IN PRESS BOX. CABLE SHALL BE BY PAGE DATA "GAME  
CHANGER", OR APPROVED EQUIV.
- 19 TEMPORARILY REMOVE DEVICES DURING CONSTRUCTION AND STORE FOR FUTURE  
INSTALLATION. REMOVE EXISTING ASSOCIATED FOUNDATIONS AND BOLLARDS. PULL  
ASSOCIATED WIRING BACK TO SAFE POINT AT THE EDGE OF CONSTRUCTION. THEN RE-ROUTE  
CONDUITS TO NEW LOCATIONS. REINSTALL AND RECONNECT EQUIPMENT.