




1
A-F2
TYPICAL WALL PADDING DETAIL @ EXISTING BLEACHERS
SCALE: 1-1/2\"/>



2
A-F2
WALL PAD CORNER AT
EXPANSION JOINT DETAIL PLAN
SCALE: 1-1/2\"/>




3
A-F2
TYPICAL WALL PADDING DETAIL
SCALE: 1-1/2\"/>



4
A-F2
WALL PAD CORNER DETAIL PLAN
SCALE: 1-1/2\"/>



NOTE: GC SHALL NEATLY CUT PADDING AT ALL ELECTRICAL DEVICES, LOUVERS, FIRE EXTINGUISHERS, ETC. AND WRAP FABRIC AT ALL CUTS.
(TYP. FOR ALL PADDING LOCATIONS)



FIRST FLOOR PLAN - UNIT F
SCALE: 1/8\"/>

- GYMNASIUM FLOOR REFINISHING NOTES
1. EXISTING BLEACHERS SHALL BE REMOVED, INCLUDING ANY INTEGRAL ELECTRICAL CONNECTIONS AND SERVICES. TO ALLOW REFINISHING OF FLOORING UNDER BLEACHERS WITHOUT SIGNIFICANT DISASSEMBLY, BLEACHERS AND ALL POWER AND CONTROL WIRING SHALL BE REINSTALLED, TESTED, AND VERIFIED TO BE OPERABLE SO AS TO ENSURE SAFE AND PROPER OPERATION.
 2. ALL LINES ON MAIN COURT SHALL BE 2\"/>
 3. PROTECT ALL EXISTING FINISHES, EQUIPMENT, ETC FROM DAMAGE DURING REMOVAL AND REINSTALLATION OF THE BLEACHERS AS WELL AS THROUGHOUT FLOOR REFINISHING.
 4. ALL DIMENSIONS SHOWN SHALL BE FIELD VERIFIED PRIOR TO FLOOR SANDING, REFINISHING AND RESTRIPIING NEW LAYOUT. THE THE CONTRACTOR SHALL PROVIDE A COPY OF THE PROPOSED LAYOUT AND COLORS TO THE ARCHITECT AND OWNER FOR APPROVAL PRIOR TO FINAL LAYOUT. ANY CORRECTIONS IN THE LINE LAYOUT REQUIRED SHALL BE ACCOMMODATED BY THE CONTRACTOR AT NO EXTRA COST. LINE STRIPING SHALL BE ESTABLISHED FROM THE EXISTING BACKBOARDS AND SPORTS EQUIPMENT THAT ARE TO REMAIN.
 5. THE REMOVAL AND REINSTALLATION OF THE BLEACHERS WILL AFFECT THE SEQUENCE OF THE FLOOR REFINISHING, AND AS SUCH, THE CONTRACTOR IS TO FAMILIARIZE THEMSELVES WITH THE PROCEDURES FOR BLEACHER REMOVAL AND REINSTALLATION IN ORDER TO ENSURE PROPER COORDINATION OF THIS WORK. ALL WORK INVOLVING BLEACHERS IS TO BE PERFORMED BY A FACTORY-TRAINED OR AUTHORIZED BLEACHER INSTALLER/SERVICE TECHNICIAN. THE RECOMMENDED SEQUENCE FOR BLEACHER REMOVAL/ REINSTALLATION IS AS FOLLOWS:
 - A. REMOVE EXISTING BLEACHER AND RELOCATE TO ALLOW REFINISHING OF THE FLOOR. COORDINATE WITH THE OWNER FOR TEMPORARY STORAGE LOCATION.
 - B. RELOCATE BLEACHERS TO AND FROM THEIR ORIGINAL LOCATION BY USE OF RAMPING TO COMPENSATE FOR ANY VARIATION IN FLOOR ELEVATIONS.
 - C. UPON COMPLETION OF FLOOR REFINISHING, BLEACHERS ARE TO BE INSPECTED, ADJUSTED AND RETURNED TO THEIR OPERATION CONDITION BY AN INDUSTRY EXPERT

REFER TO DRAWING A-22 FOR TYPICAL SCHEDULES, LEGENDS AND RENOVATION NOTES
REFER TO DRAWING A-24, A-25 FOR TYPICAL DETAILS.



AEM ARCHITECTS, INC.
3700 PERKINS AVENUE, READING, PA 19606-2785
Phone: 610.779.3320 Fax: 610.779.8022 www.aem-arch.com

1/8\"/>

JOB NO.: 23001.00
DRAWN BY: SRH
DATE: 04.12.24

A-F2