



CEILING EQUIPMENT LEGEND	
SYMBOL	DESCRIPTION
	HVAC RETURN GRILLE
	HVAC DIFFUSER
	EXHAUST GRILLE
	PROJECTOR
	WIFI DEVICE
	EXIT SIGN
	LIGHT FIXTURE
	LIGHT FIXTURE
	CAMERA
	SMOKE / HEAT DETECTOR
	SPRINKLER HEAD
	SPEAKER
	TV MOUNT
	POWER DROP
	FIRE ALARM AUDIO/VISUAL UNIT
	FIRE ALARM VISUAL UNIT
	FIRE ALARM AUDIO UNIT
	OCCUPANCY SENSOR
	DAYLIGHT SENSOR

CEILING TYPE LEGEND	
SYMBOL	DESCRIPTION
	GYPSUM BOARD (PTD.)
	2' X 2' ACOUSTICAL TILE CEILING - TYPE 1
	2' X 4' ACOUSTICAL TILE CEILING - TYPE 1
	2' X 4' ACOUSTICAL TILE CEILING - TYPE 2
	2' X 4' ACOUSTICAL TILE CEILING - TYPE 3
	EXPOSED STRUCTURE
	EXISTING CONCRETE CEILING TO REMAIN
	EXISTING CEILING TO REMAIN
	RECOAT EXISTING EIFS (INCLUDING VERTICAL SURFACES)
BULKHEAD TYPE LEGEND	
SYMBOL	DESCRIPTION
	GYP. BD. BULKHEAD (DETAIL 1/A-13A)
	EXISTING GYP. BD. BULKHEAD TO REMAIN (PTD.)
REFER TO ROOM FINISH SCHEDULES FOR CEILING HEIGHTS.	
GENERAL NOTES	
A. IN CANOPIES TO REMAIN, GC SHALL FASHION COVER PLATE AT LOCATIONS WHERE LIGHTS ARE BEING REMOVED. COVER PLATE SHALL BE .040 ALUMINUM MINIMUM AND SHALL PROVIDE SUFFICIENT SUPPORT FOR NEW LIGHT FIXTURE INSTALLATION. COVER PLATE SHALL BE FINISHED TO MATCH EXISTING CEILING AS CLOSELY AS POSSIBLE.	
B. EXPANSION JOINTS IN CEILINGS SHALL BE REPLACED AT ALL BUILDING EXPANSION CONDITIONS.	



PARTIAL SECOND FLOOR REFLECTED CEILING PLAN - UNIT E  
SCALE: 1/8" = 1'-0"



REFER TO DRAWING A-22 FOR TYPICAL SCHEDULES, LEGENDS AND RENOVATION NOTES  
REFER TO DRAWING A-24, A-25 FOR TYPICAL DETAILS.